

APC Smart-UPS VT Maintenance Bypass Panel 10-20kVA 400V Wallmount



APC Smart-UPS Accessories , Input: 400V 3PH , Output: 400V 3PH

Includes: Installation guide, User Manual

Output

Nominal Output Voltage

400V 3PH

Input

Nominal Input Voltage

400V 3PH

Input Frequency

50 Hz +/- 3 Hz

Number of Power Cords

1

Physical

Net Weight

7.01 KG

Maximum Height

315.00 mm

Maximum Width

305.00 mm

Maximum Depth

175.00 mm

Shipping Weight

7.73 KG

Shipping Height

442.00 mm

Shipping Width

305.00 mm

Shipping Depth

175.00 mm

Color

Grey

Units per Pallet

1.00

Environmental

Operating Environment

0 - 40 °C

Operating Relative Humidity

0 - 95%

Operating Elevation

0-15000 meters

Storage Temperature

0 - 40 °C

Storage Relative Humidity

0 - 95%

Storage Elevation

0-15000 meters

Conformance

Regulatory Approvals

EN 50091-2,EN/IEC 62040-3,EN/IEC 62040-1-1

Standard Warranty

1 year (parts only)

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[About Schneider Electric](#)[Investors](#)[Job](#)

[Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy](#) [Policy](#)