



## ProtectNet

# APC ProtectNet standalone surge protector for Serial RS232 lines (9 pin female to male)



Advanced Protection Against Damaging Power Transients Traveling Over Computer, AV and Network Data Lines

**Includes:** User Manual

**Standard Lead Time:** Usually in Stock

### Surge Protection and Filtering

Peak Current Common Mode

0.20 kAmps

NM Surge Response Time (ns)

1 ns

Data Lines Protected

(multi-line only)

1-9

Let Through Voltage Rating

< 40

### Physical

Net Weight

0.06 KG

Maximum Height

76.00 mm

Maximum Width

36.00 mm

Maximum Depth

15.00 mm

Shipping Weight

0.10 KG

Shipping Height

178.00 mm

Shipping Width

165.00 mm

Shipping Depth

44.00 mm

Master Carton Units

40.00

Color

Beige

**Environmental**

Operating Environment

-15 - 45 °C

Operating Relative Humidity

0 - 95%

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

0 - 95%

**Conformance**

Regulatory Approvals

UL 497B,UL Listed

Standard Warranty

Lifetime

Environmental Compliance

RoHS

\*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[About Schneider Electric](#)[Investors](#)[Job](#)

[Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)