

## ProtectNet

### **APC ProtectNet standalone surge protector for analog/DSL phone lines (2 lines, 4 wires)**



Advanced Protection Against Damaging Power Transients Traveling Over Computer, AV and Network Data Lines

**Includes:** User Manual

#### Input

Input Connections

--

#### Surge Protection and Filtering

Peak Current Normal Mode

0.20 kAmps

Peak Current Common Mode

0.15 kAmps

NM Surge Response Time (ns)

1 ns

Data Line Protection

RJ-45 Modem/Fax/DSL protection (four wire dual line)

Data Lines Protected

(multi-line only)

3-6 RJ45

Let Through Voltage Rating

< 260

#### Physical

Net Weight

0.06 KG

Maximum Height

103.00 mm

Maximum Width

47.00 mm

Maximum Depth

28.00 mm

Shipping Weight

0.14 KG

Shipping Height

104.00 mm

Shipping Width

90.00 mm

Shipping Depth

29.00 mm

Master Carton Units

144.00

Master Carton Weight

18.00 lbs.

SCC Codes

10731304000430

Color

Beige

Units per Pallet

750.00

**Environmental**

Operating Environment

-15 - 45 °C

Operating Relative Humidity

0 - 95%

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

0 - 95%

**Conformance**

Regulatory Approvals

CSA,UL 497A,UL Listed

Standard Warranty

10 years repair or replace

Environmental Compliance

RoHS

\*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[About Schneider Electric](#)[Investors](#)[Job](#)

[Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy](#) [Policy](#)