



APC Smart-UPS XL 48V RM 3U Battery Pack



Output

battoutvolt
48

Batteries & Runtime

Battery Volt-Amp-Hour Capacity
1728

Battery Type

Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Battery mounting

Enclosed battery cartridge

Battery manufacturer

--

Expected Battery Life (years)

3 - 5

RBC™ Quantity

2

Replacement battery cartridge note

For use with SUA 2200/3000VA 3U models. Can be used with the 5U models with SUA039 extension cable.

Battery blocks per string

4

Physical

Net Weight

63.64 KG

Maximum Height

133.00 mm

Maximum Width

483.00 mm

Maximum Depth

660.00 mm

Shipping Weight

72.00 KG

Shipping Width

610.00 mm

Shipping Height

280.00 mm

Shipping Depth

980.00 mm

Rack Height

3U

Color

Black

Units per Pallet

8.00

Environmental

Operating Environment

0 - 40 °C

Operating Relative Humidity

0 - 95%

Operating Elevation

0-3000 meters

Storage Temperature

-15 - 45 °C

Storage Relative Humidity

0 - 95%

Storage Elevation

0-15000 meters

Conformance

Standard Warranty

2 years repair or replace

Environmental Compliance

RoHS

*Except where noted, all prices are Estimated Resale Price (ERP) - Without Tax/VAT. Pricing in other locations and sites may vary.

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[About Schneider Electric](#)[Investors](#)[Job](#)

[Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)