

Key **Features**

- Advanced ergonomics with a 40° tilt,
 130mm height adjustment, ±60°swivel, and ±90°pivot
- Flexible connectivity with DisplayPort, HDMI, VGA, and USB 3.2
- TCO & Energy Star certificated
- Versatile stand design for mounting a mini-PC or cloud client



Product **Description**

ViewSonic VG2448a-2 is a 24" Full HD monitor with productivity-enhancing features including IPS technology and an advanced ergonomic design for the modern-day office. Utilising SuperClear® IPS panel technology and 1080P resolution, VG2448a-2 delivers a crisp, clear image from any viewing angle. An advanced ergonomic design offers the widest range of customisable adjustments currently available to provide maximum comfort, including pivot, swivel, height adjustment, and an impressive 40° tilt, which enables you to use the monitor while standing and to have strategic group discussions around the screen. VG2448a-2 uses environmentally friendly packaging and offers a quick and easy out-of-the-box set-up via the quick release stand. The cloud client mounts on the back of the monitor stand coupled with cable management design features make VG2448a-2 perfect for deployment in cloud-based environments. Versatile connectivity options include HDMI, DisplayPort, VGA, and USB 3.2 inputs.



Visit Us

www.viewsonic.com

DISPLAY		VIDEO INPUT	
Display Size (in.):	24	Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
Viewable Area (in.):	23.8	Analan Coma	Separate/Composite/SOG - RGB
Panel Type:	IPS Technology	Analog Sync:	Analog
Resolution:	1920 x 1080	ERGONOMICS	
Resolution Type:	FHD	Height Adjust (mm):	130
Static Contrast Ratio:	1,000:1 (typ)	Swivel:	120°
Dynamic Contrast Ratio:	50M:1	Tilt (Forward/Back):	-5° / 40°
Light Source:	LED	Pivot (Right/Left):	90° / 90°
Brightness:	250 cd/m² (typ)	WEIGHT (IMPERIAL)	
Colours:	16.7M	Net (lbs):	13
Colour Space Support:	8 bit (6 bit + A-FRC)	Net Without Stand (lbs):	7.1
Aspect Ratio:	16:9	Gross (lbs):	18.1
Response Time (Typical GTG):	5ms	WEIGHT (METRIC)	
Response Time (GTG w/OD):	5ms	Net (kg):	5.9
Viewing Angles:	178° horizontal, 178° vertical	Net Without Stand (kg):	3.2
Backlight Life (Hours):	30000 Hrs (Min)	Gross (kg):	8.2
Curvature:	Flat	DIMENSIONS (IMPERIAL) (V	VXHXD)
Refresh Rate (Hz):	60	Packaging (in.):	23.4 x 15.6 x 8.3
Blue Light Filter:	Yes	Physical (in.):	21.2 x 15.99~20.15 x 8
Flicker-Free:	Yes	Physical Without Stand (in.):	21.2 x 12.6 x 2
I HONGI-FIEG.	NTSC: 72% size (Typ)sRGB: 102%	DIMENSIONS (METRIC) (WX	HXD)
Colour Gamut:	size (Typ)	Packaging (mm):	595 x 396 x 210
Pixel Size:	0.275 mm (H) x 0.275 mm (V)	Physical (mm):	539 x 406.19~511.9 x 202
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	539 x 320 x 52
COMPATIBILITY		GENERAL	
PC Resolution (max):	1920x1080		cTUVus, FCC-B, ICES003, Energy
Mac® Resolution (max):	1920x1080	Regulations:	Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS,
PC Operating System:	Windows 10/11 certified; macOS tested	1 togulations.	ErP, REACH, WEEE, TCO 9.0, EAC, UkrSEPRO, UKCA
Mac® Resolution (min):	1920x1080	VG2448A-2 x1, 3-pin Plug (IEC C13	
CONNECTOR	192041000	PACKAGE CONTENTS:	CEE22) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB A/B Cable (v3.2 Male-Male) x1, Quick Start Guide x1
VGA:	1	Recycle/Disposal:	Please dispose of in accordance with
USB 3.2 Type A Down Stream:	4	Recycle/Disposal.	local, state or federal laws.
USB 3.2 Type B Up Stream:	1	Warranty:	*Warranty offered may differ from market to market
HDMI 1.4:	1	Power Management:	Energy Star standards
DisplayPort:	1	J	3,
Power in:	3-pin Socket (IEC C14 / CEE22)		
AUDIO			
Internal Speakers:	2Watts x2		
POWER			
Eco Mode (Conserve):	12.2W		
Eco Mode (optimised):	14.13W	-	
Consumption (typical):	16.6W		
Consumption (max):	20W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE	оа. голог очрргу		
Kensington Lock Slot:	1		
Cable Organisation:	Yes		
CONTROLS	.50		
	Key 1 (eye), Key 2, Key 3, Key 4, Key		
Physical Controls:	5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		
WALL MOUNT			
VESA Compatible:	100 x 100 mm		
INPUT SIGNAL			
Frequency Horizontal:	24 ~ 82KHz		

Copyright © ViewSonic Corporation 2000-2022. All rights reserved.

50 ~ 75Hz

Frequency Vertical: