Dell EMC PowerEdge R650xs

Spec Sheet

Purpose-built 1U server for dense, fast growing scale-out solutions

The Dell EMC PowerEdge R650xs, with 3rd generation Intel® Xeon® Scalable processors, designed to meet a specific set of requirements for medium-duty workloads with enterprise-class performance and capabilities.



Innovate at scale with challenging and emerging workloads

The new Dell EMC PowerEdge R650xs is a 1U, dual-socket server that's purpose-built to maximize value with distinctive feature sets for scale-out environments. With it, you can:

- Add additional power and cores: Up to two 3rd generation Intel® Xeon® Scalable processors, up to 32 cores per socket
- · Accelerate in-memory workloads: Up to 16 DDR4 RDIMMS, 3200 MT/sec
- Improve throughput, reduce latency: With up to 5 PCIe Gen4 slots, OCP 3.0 for network cards, and SNAP I/O support
- Include flexible storage: Up to 12x 3.5" SAS/SATA HDDs or SSDs; or up to 16x 2.5" SAS/SATA HDDs or SSDs, and 8 NVMe drives
- · Enable virtualization, medium VM density or VDI, and software-defined storage node workloads

Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools for multiple operating environments, from on-premise to cloud to edge

Built-in proactive resilience through a complete portfolio of solutions

From the silicon and supply chain all the way to asset retirement, know that your servers are safe and secure with innovative Dell EMC and Intel technologies. We give you the confidence of cyber resilience with enterprise-class security that minimizes risk for any organization, from small business to hyperscale.

- Stay strong with continuous innovations that bolster cyber resilience, like OpenManage Secure Enterprise Key Manager and Automatic Certificate Enrollment
- Outmaneuver threats with intelligence, automation, and recovery tools that include iDRAC9 Telemetry, BIOS live scanning, and Rapid OS recovery
- Start strong with platform security features, even before the server is built, including Secured Component Verification and Silicon Root of Trust

PowerEdge R650xs

The Dell EMC PowerEdge R650xs offers compelling performance, highspeed memory and capacity, I/O bandwidth and storage to address data requirements – Ideal for:

- Virtualization/Cloud
- Scale-out Database
- High-Performance Compute

Feature	Technical Specifications		
Processor	Up to two 3rd Generation Intel Xeon Scalable processors with up to 32 cores		
Memory	 16 DDR4 DIMM slots, supports RDIMM 1 TB max, speeds up to 3200 MT/s 		
	Supports registered ECC DDR4 DIMMs only		
Storage controllers	Internal controllers: PERC H345, PERC 355, PERC H745, PERC H755, PERC H755N, HBA355i, S150		
	 Internal Boot: Internal Dual SD Module, Boot Optimized Storage Subsystem (BOSSS1): HWRAID 2 x M.2 SSDs, USB External PERC (RAID): PERC H840, HBA355e 		
Drive Bays	Front bays:		
Drive Days	0 drive bay		
	Up to 4 x 3.5-inch SAS/SATA (HDD/SSD) max 64 TB		
	• Up to 8 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 61.44 TB		
	Up to 10 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 76.8 TB		
	Rear bays:		
Power Supplies	Up to 2 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 15.36 TB 600 W DC/240 V		
Tower Supplies	 600 W Platinum AC/100 - 240 V 		
	• 800 W DC/240 V		
	• 800 W Platinum AC/100 - 240 V		
	• 1100 W DC/-48–(-60) V		
	 1100 W DC/240 V 1100 W Titanium AC/100, 240 V 		
	 1100 W Titanium AC/100 - 240 V 1400 W DC/240 V 		
	 1400 W Platinum AC/100 - 240 V 		
Cooling options	Air cooling		
Fans	Standard (STD) fans, High performance SLVR fans or High performance GOLD fans		
	Up to seven cabled fans		
Dimensions	 Height – 42.8 mm (1.68 inches) Withthe 400 mm (40.07 inches) 		
	 Width – 482 mm (18.97 inches) Depth – 734.95 mm (28.92 inches) – without bezel 		
	748.79 mm (29.47 inches) – with bezel		
Form Factor	1U rack server		
Embedded Management	• iDRAC9		
	iDRAC Service Module		
	iDRAC Direct Quick Sync 2 wireless module		
Bezel	Optional LCD bezel or security bezel		
OpenManage Software	OpenManage Enterprise		
	OpenManage Power Manager plugin		
	OpenManage SupportAssist plugin		
A. 1.111	OpenManage Update Manager plugin		
Mobility Integrations and Connections	OpenManage Mobile • BMC Truesight	IBM Tivoli Netcool/OMNIbus	
Integrations and connections	Microsoft System Center	IBM Tivoli Network Manager IP Edition	
	OpenManage Integrations	Micro Focus Operations Manager	
	Red Hat Ansible Modules	OpenManage Connections	
	VMware vCenter and vRealize Operations Manager	Nagios Core	
Convitu	- Chuntagraphically signed firmulare	Nagios XI	
Security	Cryptographically signed firmwareSecure Boot		
	Secure Erase		
	Silicon Root of Trust		
	System Lockdown (requires iDRAC9 Enterprise or Datacenter)		
	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China National Control of the second	tionZ	
Embedded NIC	2 x 1 GbE LOM 1 x OCP 3.0		
Network Options GPU Options	Not supported		
Ports	Front Ports	Rear Ports	
	1 x iDRAC Direct (Micro-AB USB) port	• 1 x USB 2.0	
	• 1 x USB 2.0	• 1 x Serial (optional)	
	• 1 x VGA	• 1 x USB 3.0	
		2 x Ethernet 1 x VGA	
	Internal Ports		
	• 1 x USB 3.0 (optional)		
PCIe	Up to 3 x PCIe Gen4 slots		

Feature	Technical Specifications	
Operating System and Hypervisors	Canonical Ubuntu Server LTS	
	Citrix Hypervisor	
	Microsoft Windows Server with Hyper-V	
	Red Hat Enterprise Linux	
	SUSE Linux Enterprise Server	
	VMware ESXi	
	For specifications and interoperability details, see Dell.com/OSsupport.	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit Dell.com/OEM.	

Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit www. delltechnologies.com/Services.

Dell Technologies on demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit: www. delltechnologies.com/ondemand.

Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions







Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

© 2021 Dell Inc. or its subsidiaries. All Rights Reserved. Dell, EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. April 2021

DCLTechnologies