

Name	Anker 737 Charger (GaNPrime 120W)
SKU	A2148
	120W. IQ4 (PPS 2.0 support)
Port	3 Ports
Picture	
Main compatible devices	<p>Phones</p> <p>iPhone 12mini/12/12pro/12pro max / 11 / 11 Pro / 11 Pro Max / XS / XS Max / XR / X / 8 Plus / 8 / 7 / 6</p> <p>Samsung Galaxy S9 / S9+ / S8 / S8+ / Note 8 / Note 7</p>
Input voltage	Input: 100~240V~ 1.9A, 50-60HZ
Output current & voltage	<p>Use 1 Port Output</p> <p>USB-C1(Top Port) ; USB-C2 (Middle Port)</p> <p>USB-C1/USB-C2 : 5V==3A /9V==3A /15V==3A /20V==5A (100W Max)</p> <p>USB-A : 4.5V==5A/5V==4.5A /5V==3A /9V==2A/12V==1.5A(22.5W Max)</p> <p>Use 2 Ports Output</p> <p>USB-C1+USB-C2 : 120W Max</p> <p>USB-C1+USB-A :120W Max</p> <p>USB-C2+USB-A: 24W Max</p> <p>Use 3 Ports Output</p> <p>USB-C1+USB-C2+USB-A : 120W Max</p> <p>Total Output: 120 W Max</p>
Output Port	3
How to charge your devices	<p>Connect the charger to an outlet --</p> <p>Connect your device to the relevant USB port--Start charging</p>
Current limited swtich	YES
Voltage drop compensation /Voltage boost	YES
Temperature	<p>operating: 0°C TO 25°C</p> <p>storage: -20°C TO +70°C</p>

Certification	cTUVus, CP65, DOE, CEC, FCC, IC, NRCAN, PSE, CE-LVD, CE-EMC, ERP, ROHS, CCC, REACH, CB
Protection	Output overvoltage protection (OOVP) Short circuit protection (SCP) Output over-current protection (OOCp) Reset protection (RP)
Dimensions	EU: 43* 35.35*80
Weight	EU : 203g
Notice	To access PowerIQ 4.0 fast charging via the USB-C port, use a USB-C to USB-C cable for devices with a USB-C port, or a USB-C to Lightning cable for devices with a Lightning port.