Anker 535 Portable Power Station (PowerHouse 512Wh)

Anker 535 Portable Power Station, Portable Generator 512Wh (PowerHouse 512Wh), 500W 7-Port Outdoor Generator with 2 AC Outlets, 60W USB-C PD Output, LED Light for Camping, RV, Emergencies, and More





ANKER

Key Benefits

* 6x Longer-Lasting: Rated to provide 3000 charge cycles with premium LiFePO4 batteries extends the battery lifespan by 6x more than the standard lithium-ion battery pack. A drop-proof unibody structure enhances durability in the harshest environment for peace of mind at home or outdoors.

* Extra USB-C Port: Recharge to 80% in under 2.5 hours via the in-box adapter and a USB-C port. Time to get rid of bulky adapters because charging your laptop at fast speeds only requires a single cable.

* 7 Ports for All: The power station has all the ports you need to charge your devices and appliances. It is equipped with 2 AC ports, 3 USB-A ports, a USB-C port, and a car outlet.

Bullet Selling Points

- * Support Sustainable Solar Charging
- * Quick Recharge under 2.5h
- * Built-in 60W USB-C Power Delivery
- * Illuminate The Way
- * Smart LED display

Brand Name: Anker

Product Dimensions: 292 x 251 x 188 mm/ 11.5 x 9.9 x 7.4 in

Product Gross Weight: 7.6 kg/ 16.8 lb

What Included

- * Anker 535 Portable Power Station
- * 120W adapter, car charging cable
- * Our worry-free 5-Year warranty

Attribute Name Values

Cell Capacity: 512Wh

Lifecycle: 3000 cycles to 80%+ capacity

© Anker Innovations Limited. All rights reserved. Anker, the Anker logo, PowerCore, PowerPort, PowerLine, PowerWave, PowerDrive, PowerIQ, VoltageBoost, and MultiProtect are trademarks of Anker Innovations Limited. All other trademarks are the property of their respective owners.

ANKER

Product Picture	
Product Name	Anker 535 Portable Power Station (PowerHouse 512Wh)
Product PN #	A1751311
EAN	0194644098636
Battery Information	LiFePO4
Type of Battery Capacity (Wh)	512Wh
Capacity (Wh)	160000mAh
Cycle Life	3000+ (to 80%)
Power left after 1-year without using (from 100%)	51%
RechargeInformation	•
Input Votage	100 -240V
Total Input Power	180W (1x 60PD + 120W Adapter)
EST Recharge Time with DC Adapter+ PD	3.4hrs (1x 60PD + 120W Adapter)
Use Ports While Recharging	Yes
Direct ACInput MaximumAC Input Power	No
# of DC Input	1
DCAdapter	Yes
DC Adapter Input Power	11-28V 10A (120W Max)
EST DC Adapter Recharge Time	4.5hrs
DC Input Size	7909
# of PD Input	1
PDInput Power	5V=3A; 9V=3A; 15V=3A; 20V=3A (60W Max)
EST PDRecharge Time	9.5 Hours (1x 60W PD)
#of Anderson Input	-
Maximum Anderson Input Power	•
Solar Input Power	11-28V [~] 10A (120W Max)
EST Solar Recharge Time	4.5hrs (120W) 5.4hrs(100W)
Solar Panel Compatible	Yes
MPPT Support Output Information	Yes
Maximum Output	716W
#of Output Ports	7 (For EU)
# of ACSocket	2 (For EU)
AC Rated Power	500W
AC Surge Power	750W
AC Total Output	500W
AC Auto Shut-Off	Power Save Mode On (2hr)
# of USB-A Output	3
USB-A Rated Power (per port)	5V=2.4A (12W Max)
USB- A Total Output # of USB-C Output	36W 1
USB -C Rated Power (per port)	5V=3A; 9V=3A; 15V=3A; 20V=3A (60W Max)
USB-C Total Output	60W
USB auto shut-off	Yes
# of Car Outlet	1
Car Outlet Rated Power (per port)	10.8~14V=10A (120W Max)
Illumination Information	
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode SOS Mode
Screen Display Information	
LCD Display % of Power	Yes
Total Input Power	Yes
EST Time to Fully Recharge	Yes Yes
Total Output Power	Yes
EST Time to Deplete	Yes
Input Ports	Yes
Output Ports	Yes
High-Temperature Alram	Yes

Low-Temperature Alram	Yes
LCD Display auto shut-off	Yes
Power Saving Mode	Yes
APP Connect	No
Remaining Battery for Expansion Battery	No
Display Time before auto shut-off (with no operation to the powerhouse)	30s
What You Get	
AC Adapter	1x 120W Adapter
Cable	Car Charging Cable
Weight & Dimension	
Product Dimension (mm)	292 x 251 x 188 mm
Product Weight (kg)	7.6 kg
Product Weight with Package (kg)	8.87 kg
Product Weight	9.4 kg
Safty Information	
Ingress Protection (Dust/Water Protection Level)	No
Operation Temperature (°C/° F)	Charging: -20 -40°C Recharging: 0-40°C
Overload Protection (AC)	>550W
Over-current Protection (USB -A)	>2.4A
Over-current Protection (USB- C)	>3.6A
Over-current Protection (DC)	>10A
Rechargetime	
recharge to 80%	DCOnly: 3.2H PDOnly: 7.5H DC+PD: 2.4H
recharge to 100%	DCOnly: 4.5H PDOnly: 9.5H DC+PD: 3.4H