


<b>Product Picture</b>	
<b>Product Name</b>	<b>Anker 555 Portable Power Station</b>
<b>Product PN #</b>	<b>A1760311</b>
<b>Battery Information</b>	
Type of Battery	LiFePO4
Capacity (Wh)	1024Wh
Capacity (mAh)	32000mAh
Cycle Life	3000+ (to 80%)
Power left after 1- year without using (from 100%)	52%
<b>Recharge Information</b>	
Input Voltage	100-240V
Total Input Power	300W (1x 100PD + 200W Adapter)
EST Recharge Time with DC Adapter + PD	4.1hrs (1x 100PD + 200W Adapter)
Use Ports While Recharging	Yes
Direct AC Input	No
Maximum AC Input Power	-
# of DC Input	1
DC Adapter	Yes
DC Adapter Input Power	11-28V= 10A (200W Max)
EST DC Adapter Recharge Time	5.5hrs
DC Input Size	7909
# of PD Input	1
PD Input Power	5V=3A/ 9V =3A/ 15V=3A/20V=3A/20V=5A
EST PD Recharge Time	12 Hours (1x 100W PD)
# of Anderson Input	-
Maximum Anderson Input Power	-
Solar Input Power	11-28V= 10A (200W Max)
EST Solar Recharge Time	5.5hrs (200W) 11.2hrs(100W)
Solar Panel Compatible	Yes
MPPT Support	Yes
<b>Output Information</b>	
Maximum Output	1364W
# of Output Ports	12 (For US/JP) 8 (For CN/EU/UK)
# of AC Socket	6 (For US/JP)
AC Rated Power	1000W
AC Surge Power	1500W
ACTotal Output	1000W
AC Auto Shut-Off	Power Save Mode On (2hr)
# of USB-A Output	2

USB-A Rated Power (per port)	5V=2.4A (12W Max)
USB-A Total Output	24W
# of USB-C Output	3
USB-C Rated Power (per port)	5V=3A/ 9V =3A/ 15V=3A/20V=3A/20V=5A (100W Max)
USB-C Total Output	220W
USB auto shut-off	Yes
# of Car Outlet	1
Car Outlet Rated Power (per port)	10.8~14V=10A
<b>Illumination Information</b>	
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode SOS Mode
<b>Screen Display Information</b>	
LCD Display	Yes
% of Power	Yes
Total Input Power	Yes
EST Time to Fully Recharge	Yes
Total Output Power	Yes
EST Time to Deplete	Yes
Input Ports	Yes
Output Ports	Yes
High-Temperature Alarm	Yes
Low -Temperature Alarm	Yes
LCD Display auto shut -off	Yes
Power Saving Mode	Yes
APP Connect	No
Remaining Battery for Expansion Battery	No
Display Time before auto shut -off (with no operation to the powerhouse)	30s
<b>What You Get</b>	
AC Adapter	1x 200W Adapter
Cable	Car Charging Cable 100cm Solar Charging
<b>Weight &amp; Dimension</b>	
Product Dimension (mm)	350 x 295 x 188 mm
Product Weight (kg)	13.1 kg
Product Weight with Package (kg)	15.2 kg
Product Weight for Transportation (with UN Box)	16.2 kg
<b>Safety Information</b>	
Ingress Protection (Dust/Water Protection Level)	No
Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104 °F Recharging: 0 -40°C / 32-104 °F
Overload Protection (AC)	>550W
Over-current Protection (USB-A)	>2.4A
Over-current Protection (USB-C)	>3.6A
Over -current Protection (DC)	>10A
<b>Recharge time</b>	

recharge to 80%	120W Car Socket: 7.2h 100W PD Only: 8.8h 200W Adaptor: 4.2h 200W Adaptor+100W PD: 2.8h
recharge to 100%	120W Car Socket: 9.8h 100W PD Only: 11.4h 200W Adaptor: 5.5h 200W Adaptor+100W PD: 4.4h