



 Lexmark™

CS521dn

Reliability. Security. Productivity.



CS521dn



Lexmark CS521dn

High-yield replacement toner and tools that help minimise toner consumption are the Lexmark CS521dn's keys to controlling the cost of colour. Built for reliability, performance and security, the CS521dn prints at up to 33 pages per minute* and features long-life imaging unit and optional maximum input of up to 1,451 pages.



Ready when you are

- ▶ A 1-GHz dual-core processor and 1 GB memory drives printing at up to 33 ppm*.
- ▶ The steel frame and durable design stands up to heavy use and harsh environments.
- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 7,000 colour and 10,500 monochrome pages**.
- ▶ Keep printing in black even when colour toner is empty.

Colour that keeps saving

- ▶ PANTONE® calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- ▶ Save toner with suite of tools that let you choose when and how much colour to print.

Input that works

- ▶ Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- ▶ 251 pages of standard input can grow to 1,451.

Interact with ease

- ▶ The 6 cm colour LCD lets you configure, interact and monitor vital system information.
- ▶ A front USB port allows walk-up printing from popular file formats without a computer.
- ▶ The compact footprint allows flexible placement in more locations.
- ▶ Connect easily via Ethernet, USB, or simple mobile printing options.

Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe - in the document, on the device and over the network.
- ▶ Keypoint Intelligence - Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.
**Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information.
***Award based on Western Europe data

Lexmark CS521dn



- 1 CS521dn 6 cm LCD
308 x 442 x 421 mm
- 2 650-sheet duo tray
133 x 424 x 416 mm
- 3 550-sheet tray
133 x 424 x 416 mm

Adjustable printer stand (not shown)
521 x 653 x 625 mm

Swivel cabinet (not shown)
263 x 476 x 600 mm

- Standard
- Optional

Note 1: Supports one optional 650-sheet duo tray; or one optional 650-sheet duo tray and one optional 550-sheet tray with the 650-sheet duo tray on top.
Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE®, PANTONE® Goe™ and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

Product specifications
Lexmark CS521dn
Printing

Display	6 cm (2.4-inch) Colour LCD display
Print Speed: Up to ⁶	Black: 33 ppm / Colour: 33 ppm
Time to First Page: As fast as / Time to First Page: as fast as	Black: < 7.5 seconds / Colour: < 7.5 seconds
Print Resolution	Black: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi) / Colour: 1200 x 1200 dpi, 4800 Colour Quality (2400 x 600 dpi)
Memory / Processor	standard: 1024 MB / maximum: 1024 MB / Dual Core, 1000 MHz
Hard Disk	Option available
Recommended Monthly Page Volume ²	1,500 - 8,500 Pages
Maximum Monthly Duty Cycle: Up to ³	85,000 pages per month

Supplies⁷

Laser Cartridge Yields (up to) ¹	5,000-page Colour (CMY) High Yield Cartridges, 8,500-page High Yield Cartridge, 7,000-page Colour (CMY) Extra High Yield Cartridges, 1,400-page Colour (CMY) Cartridges, 2,000-page Black Cartridge, 10,500-page Black Extra High Yield Cartridge
Photoconductor Estimated Yield: Up to ⁵	125,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product ¹	2,000-page Colour (CMY) Return Programme Toner Cartridges, 3,000-page Black Starter Return Programme Toner Cartridge

Paper Handling

Included Paper Handling	250-Sheet Input, 125-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed
Optional Paper Handling	550-Sheet Tray, 550-Sheet Duo Tray with 100-Sheet Feeder
Paper Input Capacity: Up to	Standard: 250+1 pages 75 gsm bond / Maximum: 1,450+1 pages 75 gsm bond
Paper Output Capacity: Up to	Standard: 125 pages 75 gsm bond / Maximum: 125 pages 75 gsm bond
Media Types Supported	Card Stock, Paper Labels, Plain Paper, Vinyl Labels
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, C5 Envelope, DL Envelope, B5, Hagaki Card, Executive, Folio, Legal, Universal, Oficio

General Information⁴

Standard Ports	USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Specification Hi-Speed Certified port (Type A)
Optional Network Ports	MarkNet N8352 802.11b/g/n Wireless, Marknet N8372 WiFi Option
Noise Level: Operating	Print: 50 dBA
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3,048 Metres (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)
Product Guarantee	1-Year Onsite Repair, Next Business Day
Size (mm - H x W x D) / Weight	308 x 442 x 421 mm / 21 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.