# ViewSonic®

LED DISPLAY
VA2432-h

Key **Features**

- HDMI and VGA Input
- SuperClear® IPS Technology for rich colors at wide angles
- 75Hz Refresh rate delivers fluid visuals
- Eye-Care technology for comfortable viewing
- Eco-mode for low energy consumption

Product **Description**

The ViewSonic VA2432-h is a 24" Full HD IPS monitor with HDMI and VGA input for business or home usage. With SuperClear® IPS technology and Full HD resolution, images are clear and detailed from a wide range of viewing angles. The VA2432-h's three-sided frameless bezel design delivers a seamless viewing experience. This monitor provides six ViewMode presets that deliver optimized screen performance in different applications. Eye-Care technology and energy-saving Eco mode help to eliminate eye strain from extended viewing periods. With VESA-compatible mount support, this monitor is easy to setup in any environment.

540mm · 406mm · 23.8" · 323mm · 36mm · 185mm

1. Menu Control Panel
2. HDMI
3. VGA
4. VESA Compatible (Wall Mount 75x75mm)
5. AC IN

Visit **Us**   www.viewsonic.com

DISPLAY

Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ), sRGB: 104% size (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
HDMI 1.4:	1
Power in:	External power adapter

AUDIO
POWER

Eco Mode (Conserve):	15W
Eco Mode (optimized):	18W
Consumption (typical):	22W
Consumption (max):	24W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.3W
Power Supply:	External

ADDITIONAL HARDWARE

Kensington Lock Slot:	1

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	75 x 75 mm

INPUT SIGNAL

Frequency Horizontal:	24 ~ 86KHz
Frequency Vertical:	48 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-3º / 20º

WEIGHT (IMPERIAL)

Net (lbs):	6
Net Without Stand (lbs):	5.3
Gross (lbs):	8.2

WEIGHT (METRIC)

Net (kg):	2.7
Net Without Stand (kg):	2.4
Gross (kg):	3.7

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	23.6 x 15.6 x 4.4
Physical (in.):	21.3 x 16 x 7.3
Physical Without Stand (in.):	21.3 x 12.7 x 1.4

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	600 x 395 x 112
Physical (mm):	540 x 406 x 185
Physical Without Stand (mm):	540 x 322 x 36

GENERAL

Regulations:	RoHS, WEEE, BSMI, BIS
PACKAGE CONTENTS:	VA2432-H x1, HDMI Cable (v1.4; Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1, Power plug x2
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market